

Sponsor: Foster/Elliott

ORDINANCE NO. 26-19

AN ORDINANCE REPEALING AND AMENDING THE CITY OF JACKSON CODIFIED ORDINANCES SECTIONS 941.21 AND 941.26 AS ESTABLISHED BY ORD. 67-10.

WHEREAS, ORD 67-10 established certain requirements for foundations and corner and foot markers as set forth in Sections 941.21 and 941.26 of the Codified Ordinances of the City of Jackson; and

WHEREAS, the legislative authority of the City of Jackson has determined it necessary to change the requirements as shown in Exhibit A attached hereto where the revised language is shown to be struck through with the new language shown as underlined; and


NOW, THEREFORE, BE IT ORDAINED BY THE LEGISLATIVE AUTHORITY OF THE POLITICAL SUBDIVISION OF THE CITY OF JACKSON, OHIO THAT ORD 67-10 BE AMENDED AND REPEALED AND SECTIONS 941.21 AND 941.26 OF THE CODIFIED ORDINANCES OF THE CITY OF JACKSON BE AMENDED, AS SET FORTH AS ATTACHED HERETO AS EXHIBIT A, WITH THOSE STRUCK THROUGH PORTIONS BEING REMOVED AND REPLACED WITH THE UNDERLINED LANGUAGE SHOWING THE AMENDMENTS TO THE ORIGINAL LANGUAGE AND THAT IT BE REPLACED WITHIN THE JACKSON CITY CODE, IN REGULAR TEXT.

It is hereby found and determined that all formal actions of this Council concerning and relating to adoption of this ordinance were adopted in an open meeting of this Council and the deliberations of this Council and any of its committees that resulted in such formal action were in a meeting open to the public, in compliance with all legal requirements, including Section 121.22 of the Ohio Revised Code.

PASSED AND ADOPTED by the Legislative Authority of the Political Subdivision on this 12th day of August, 2019.



President of Council

ATTEST:


Clerk of the Legislative Authority

Approved this 12th day of Aug., 2019.



Mayor

EXHIBIT A

941.21 CORNER STONES AND FOOT MARKERS.

Corner stones shall not exceed eight inches in width, and shall not extend above ground level. Borders or curbing and any type of fencing, either permanent or temporary, are not allowed. Foot markers shall not extend above ground level.

941.26 POURING FOUNDATIONS.

All foundations poured in Fairmount Cemetery are to be of not less than 5 bag mix Portland Cement, Air Entrained for outdoor exposure. Foundations shall be no less than ~~twenty-four inches~~ eighteen inches deep at their shallowest depth. Said foundation shall project above the ground two inches at its lowest point. Foundations poured in sub-freezing temperature shall be protected in such a way as to insure that no freezing of the concrete shall occur. No foundation is to be poured until it is inspected as to size and depth by the Service/Safety Director or his designee. All monument bases are to be sealed to the foundations with either 100% silicone or setting compound. If not properly sealed, there will be a \$100.00 fee charged to the monument company.